


Performance

- Frequency: 2-18GHz
- Coupling: 15dB
- Coupling Flatness: 3.5dB
- Chip size: 2.5*2.3*0.1mm

Function Diagram




Electrical Specifications (Ta=+25°C, 50Ω system)


Parameter	Min	Typical	Max	Unit
Frequency Range	2-18			GHz
Coupling	13.7	15	17.2	
Insertion Loss	0.4	0.7	0.9	dB
Input Return loss	14	15	-	dB
Thru Output Return loss	14	15	-	dB
Coupling Output Return loss	13	15	-	dB

Test Curves (Die chip + Bonding line test)


Coupling vs. Freq




Insertion loss vs. Freq




Input Return Loss vs. Freq



Thru output Return loss vs. Freq



Coupling Output Return Loss




Absolute Rating

Storage Temperature	-65~+150°C
Operating Temperature	-55~+125°C
Max Input Power	1W
Static Protection (HBM)	Class 1A



Outline Size




Note:

1. Unit: um
2. Bottom side is gold plated
3. Bottom side is GND
4. Bonding pads is gold plated, Pad size: 100*100(um)
5. Don't bonding on thru holds
6. Tolerance: ±50um

Bonding Pads Definition

Number	Symbol	Description
1	RFin	RF input port, 50ohm
2	RFout	RF output port, 50 ohm
3,4	Couple/ISO	Choose either one as couple output port, another port connect to 50Ω resistor pad
5,6	Load	50Ω resistor pad

Application (Chip left side couple output)



Application (Chip right side couple output)

