


Performance

- Frequency: 5~6GHz
- Typical Signal Gain: 27dB
- Typical Pout: 41.5dBm@28V
- PAE: 55%
- Bias: 28V, -1.8V (Typ.)
- Technology: 0.25um HEMT
- Size: 2.2mm*1.6mm*0.08mm

Function Diagram




Electrical Specifications (TA=25°C, Vd=28V, Vg=-1.8V, PW=100us, D.C:10%, F: 5~6GHz, CW)


Symbol	Parameter	Min	Typical	Max	Unit
G	Small Signal Gain	-	27	-	dB
Gp	Power Gain	-	21	-	dB
Pout	Saturated Power	-	41.5	-	dBm
PAE	Power Added Efficiency	-	55	-	%
Rth	Thermal Resistance	-	4.2	-	°C/W

Test Curves


Small Signal Gain




VSWRin




Pout




PAE




Id




Ig




Pout@ Different Ta




PAE@ Different Ta




Id@ Different Ta




Ig@ Different Ta




Pout@ Different Vd




PAE@ Different Vd




Id@ Different Vd




Ig@ Different Vd




Pout@ Different Pin




PAE@ Different Pin




Id@ Different Pin



Ig@ Different Pin




Rf2@ Different Pin







Absolute Max Ratings (TA=25°C)

Symbol	Parameter	Value	Remark
Vd	Drain Voltage	32V	
Id	Drain Current	1.5A	
Vg	Grid Voltage	-10V~-1V	
Pd	DC Power	40W	
Pin	Input Power	27dBm	
Tch	Channel Temperature	225°C	
Tm	Mounting Temperature	310°C	30 s, N2 Protection
Tstg	Storage Temperature	-65~150°C	

Exceeding any one or combination of these limits may cause permanent damage.



Pads Definition

Pad	Description	Equivalent Circuit
RFin	RF Signal input, connect to 50ohm system, no need block capacitor.	
RFout	RF Signal output, connect to 50ohm system, no need block capacitor.	
VG	Amp gate bias, external 1000pF capacitor is needed	
VD	Amp drain bias, external 100pF capacitor is needed	
GND	Bottom must connect to RF and DC ground	