

## Features

SAW filter for Band 21

- High stability and reliability with good performance
- Single ended to Single ended
- Narrow and sharp pass band characteristics. RoHS compatible
- Low insertion loss and deep stop band attenuation for interference
- Package size 1.1mm\*0.9mm

## Electrical Specification


ITEM		Min.	Typ.	Max.	Unit	Note
Center Frequency			1503.4		MHz	
Insertion	@ 1495.9~1510.9 MHz		1.9	2.4	dB	
Insertion Loss	@ 1495.9~1510.9 MHz		1.9	2.2	dB	RT(25°C)
Passband Ripple	@ 1495.9~1510.9 MHz		0.7	1.2	dB	
VSWR	@ 1495.9~1510.9 MHz		1.6	2.0		
Attenuation	1~1447.9 MHz	40	62		dB	
Attenuation	48MHz	48	63		dB	Rx-Tx
Attenuation	1447.9~1462.9 MHz	49	67		dB	Tx
Attenuation	1472~1480 MHz	3.5	9.0		dB	(Rx+Tx)/2
Attenuation	1596~6044 MHz	33	37		dB	
Attenuation	1920~1980 MHz	40	42		dB	B1 Tx
Attenuation	2400~2500 MHz	40	42		dB	ISM2.4
Attenuation	4900~5950 MHz	33	42		dB	ISM 5G
Attenuation	4487.7~4532.7 MHz	35	53		dB	3f
Attenuation	5984~6044 MHz	33	42		dB	4f
Attenuation	6044~12750 MHz	5.0	8.0		dB	
Attenuation	7480~7555 MHz	30	36		dB	5f
Attenuation	8975~9065 MHz	15	22		dB	6f
Attenuation	10471~10576 MHz	5.0	8.0		dB	7f
Attenuation	1 1967~12087 MHz	5.0	9.0		dB	8f
Input / Output Impedance (Nominal)		50Ω/50Ω				

### Maximum Ratings


Rating	Symbol	Value	Unit
DC Voltage (between any Terminals)	$V_{DC}$	3	V
RF Power (in BW)	P	13dBm,2000h,50°C	
Operating Temperature Range	$T_A$	-20 ~ +85	°C
Storage Temperature Range	Tstg	-40 ~ +85	°C
Moisture Sensitivity Levels	MSL	3	

### Outline Drawing


Unit: mm




top view



bottom view



side view(left)




side view(front)

### Pin Configuration

PIN#	Description
1	Input
4	Output
2,3,5	Ground



Marking



Top View, Laser Marking

- “c1”: Part Number
- “.” Dot marking, indicates input
- “1”: Terminal 1


The first “\*”: Month Code (The code shown below varies in a 4-year-cycle)


Month	1	2	3	4	5	6	7	8	9	10	11	12
2016/2020	n	p	q	r	s	t	u	v	w	x	y	z
2017/2021	A	B	C	D	E	F	G	H	J	K	L	M
2018/2022	N	P	Q	R	S	T	U	V	W	X	Y	Z
2019/2023	a	b	c	d	e	f	g	h	i	j	k	m

The second “\*”: Date Code


Date	1st	2nd	3rd	4th	5th	6th	7th	8th	9th	10th	
Code	A	B	C	D	E	F	G	H	J	K	
Date	11th	12th	13th	14th	15th	16th	17th	18th	19th	20th	
Code	L	M	N	P	Q	R	S	T	U	V	
Date	21st	22nd	23rd	24th	25th	26th	27th	28th	19th	30th	31st
Code	W	X	Y	Z	a	b	d	e	f	g	h

Typical Frequency Response





Test Circuit



### Stability Characteristics


ITEM	Test Item	STD Reference	Test Conditions	per lot
	Preconditioning	JESD22-A113	1) Temperature Cycling, 5 cycles -40°C to 85°C; 2) Bake, 24 hrs @85±5°C; 3)Moisture Soak, Soak time and conditions per IPC/JEDEC J-STD-020 based on device MSL level; 4) Reflow, 3 reflow cycles; 5) Drying, Room ambient temperature.	All behind
1	Temperature Cycling	JESD22-A104	-40°C / +85°C ,5°C/min, 15min dwell, < 1 min transfer time,500cycles	3*25 pcs
2	High Temperature Storage	JESD22-A103	Temperature = 85°C, 1000 hours.	3*25 pcs
3	Temperature Humidity no bias	JEDEC Std A101-B	85°C 85%RH 240 hours	3*25 pcs
4	Human Body Mode ESD	JESD22-A114	Ta=25°C, ≥100V	3 pcs
5	Charge Device Mode ESD	JESD22-C101	Ta=25°C, ≥100V	3 pcs
6	Solderability	JESD22-B102	Wetting: 245°C, 5s.	22 pcs
7	Drop Test	JESD22-B111	1500 Gs, 0.5 millisecond duration, half-sine pulse.	20 pcs
8	Mechanical Shock	JESD-47	Shock pulse of 1500g with pulse duration of 0.5+/-0. 1msec (X ,Y & Z); 5 shocks per axis.	3*25 pcs

### Remarks


- SAW devices should not be used in any type of fluid such as water, oil, organic solvent, etc.
- Be certain not to apply voltage exceeding the rated voltage of components.
- Do not operate outside the recommended operating temperature range of components.
- Sudden change of temperature shall be avoided, deterioration of the characteristics can occur.
- Be careful of soldering temperature and duration of components when soldering.
- Do not place soldering iron on the body of components.
- Be careful not to subject the terminals or leads of components to excessive force.
- SAW devices are electrostatic sensitive. Please avoid static voltage during operation and storage.
- Ultrasonic cleaning shall be avoided. Ultrasonic vibration may cause destruction of components.

**Packing Information**

Carrier Tape




Reel Dimensions



Outer Packing

Type	Quantity	Dimension	Description	Weight
Carton Box I	100000	240×210×285mm	anti-static plastic bag & carton box 1 reel / bag 10 bags / box (100000pcs)	2.15kg
Carton Box II	300000	470×310×285mm	30 bags / box (300000pcs)	6.22kg

**Recommended Soldering Profile**



Remarks:

1. The specifications of this device are subject to change or obsolescence without notice.
2. Typically, equipment utilizing this device requires emissions testing and government approval, which is the responsibility of the equipment manufacturer.
3. Our liability is only assumed for the Surface Acoustic Wave (SAW) component(s) per se, not for applications, processes and circuits implemented within components or assemblies.
4. For questions on technology, prices and delivery, please contact our sales offices or e-mail [sales@sainty-tech.com](mailto:sales@sainty-tech.com).